SERIII-W
Scramble Keypad

Overview

The SERIII Scramble Keypad is a keypad reader designed to prevent onlookers from detecting the PIN code being entered. The LED's display a randomly allocated set of numbers from 0 to 9. The position of the numbers change every time the keypad is activated. Only the user standing directly in front of the keypad can see the scrambled digits.

Features and Benefits

- Very narrow viewing angle of the lighted, scrambled digits
- The membrane keypad is extremely durable
- Random allocation of digits ensures even wear to the keys
- Individual PIN codes can be up to 9 digits in length
- The SERIII has a weatherproof rating of IP65
- An audible alarm signals when a button is depressed
- Robust polycarbonate enclosure
- The unit is equipped with power-up diagnostics and self-test routine
- The SERIII is provided with Wiegand communication protocol
- Over 3.6 million unique permutations are available
- Terminal connection on the rear of the unit

Ingersoll Rand
Security Technologies

Specifications	
Dimensions	5.39″ x 4.17″ x 2.05″
Input Voltage	8 - 12 VDC
Input Current	500mA max.
Operating Temperature	5º F to 122º F
Weight	16.76 oz.
Cable Distance (Wiegand)	500′ with 22AWG 6 conductor stranded with overall shield

ORDERING INFORMATION

SERIII-W-GR - Scramble Keypad (Gray)

SERIII-W-BLK - Scramble Keypad (Black)

SMK-2-GR - Scramble Keypad Surface Mount Kit (Gray)

SMK-2-BLK - Scramble Keypad Surface Mount Kit (Black)

SSMK-2-BLK - Scramble Keypad Surface Mount Kit (ADA Compliant)

PMK-2-GR - Panel Mount Kit (Gray)

PMK-2-BLK - Panel Mount Kit (Black)

SPMK-2-GR - Panel Mount Kit w/Steel Back Box (Gray)

SPMK-2-BLK - Panel Mount Kit w/Steel Back Box (Black)

Ingersoll Rand
Security Technologies

©2012 Ingersoll Rand 004250 11/12